



## SIGNAL AND COMMAND TRANSPONDER DEVICE



## TEO SYSTEM

- TEO SYSTEM, the new proximity scanning and management system for opening residential and professional automations by means of transponder tags (TEO) or cards (Teo Card)
- The automation is opened when the TEO transponder approaches the BE.PROXY scanner which, dialoguing with the receiver, gives the command to open the gate, the door, or any controlled device
- The system operate with a frequency of 13,56 MHz, standardised all over the world
  - 250 insertable cards or tags (TEO)
  - Reading distance 2-5 cm
  - 2 programmable relay output channels
- Possibility of commanding one of the two relay outputs with a card, or both outputs with a single or double passage of the card or tag
- Possibility of memorising the cards and tags one by one with the BE.READ, or in remote mode with the BE.PROXY, using a master card



## SIGNAL AND COMMAND



**TEO**  
Transponder device key holder shaped  
Packaging: 10 pcs



**TEO CARD**  
Transponder device in card format

### Transponder device



**TO.GO2WVT**  
2 channels self-learning code transmitter with transponder.  
Available in 10 pcs packing



**TO.GO4WVT**  
4 channels self-learning code transmitter with transponder  
Available in 10 pcs packing



**BE.PROXY**  
Proximity reader for TEO/TEO CARD/TO.GO2WVT/  
TO.GO4WVT externally fitted, to be used with the BE.READ  
receiver. Reading distance 2-5 cm



**BE.READ**  
Two-channel receiver for BE.PROXY reader. With two relay  
outputs. Timed or bistable operating mode. Memory capacity  
250 cards/tags/TO.GO2WVT/TO.GO4WVT